Caltrans

DEPARTMENT OF TRANSPORTATION

Structure Maintenance & Investigations

Bridge Number : 55C0561
Facility Carried: ISLAND WAY

Location : 0.1 MI S/O DANA PT HBR D

City :

Inspection Date: 06/18/2014

Inspection Type

Routine FC Underwater Special Other

Х

Bridge Inspection Report

STRUCTURE NAME: DANA POINT HARBOR

CONSTRUCTION INFORMATION

Year Built : 1970 Skew (degrees): 0 Year Widened: N/A No. of Joints : 0 Length (m) : 62.2 No. of Hinges : 0

Structure Description: Simply supported 4-span PC/PS concrete box girder (8 units) with a continuous RC deck and RC single column bents and RC closed end

strutted abutments, all supported upon spread footings.

Span Configuration : (S) 4 @ 15.2 m (N) c/c

SAFE LOAD CAPACITY AND RATINGS

Design Live Load: UNKNOWN

Permit Rating : PPPPP

Posting Load : Type 3: <u>Legal</u> Type 3S2: <u>Legal</u> Type 3-3: <u>Legal</u>

DESCRIPTION ON STRUCTURE

Deck X-Section: (W) 0.4 m br, 1.5 m sw, 8.5 m, 1.5 m sw, 0.4 m br (E)

Total Width: 12.5 m Net Width: 8.5 m No. of Lanes: 2 Speed: 25 mph

Min. Vertical Clearance: Unimpaired

Rail Code: 1000 Rail Description: Concrete with sidewalk.

DESCRIPTION UNDER STRUCTURE

Channel Description: Tidal basin.

INSPECTION COMMENTARY

SCOPE AND ACCESS

On the date of this inspection, piers 2 through 4 were submerged and inspected via Caltrans dive boat. All other elements were in the dry and will remain the responsibility of the assigned ABME.

NUMBERING CONVENTION

This report will reference elements using standard convention.

REVISIONS

None

SUBSTRUCTURE

The channel bottom consists of silty sand.

No scour issues were found.

ELEMENT 205 - REINFORCED CONCRETE COLUMN OR PILE EXTENSION.

Piers 2 through 4 consist of a single Reinforced Concrete "Hammerhead" Column.

Printed on: Monday 07/14/2014 08:04 AM

55C0561/AAAM/29374

INSPECTION COMMENTARY

All columns have been retrofitted with a steel mesh, which encircles the entire center section of the column, and is coated with a layer of grout approximately 100mm (4.0") thick. This retrofit covers cracks and spalls which were noted in previous inspections. Additionally, 2 sacrificial anodes, mounted horizontally and located at a depth of approximately 2.0m (6.6'), were found at the north-left and south-right quadrants. The anodes were found to be in good shape with 90% remaining.

All submerged portions were 100% covered in light marine growth 25mm (1.0") thick.

PIER 2: Maximum depth was 3.75m (12.3') at the right end with the retrofit portion extending to 1.5m (5.0') below the waterline.

PIER 3: A uniform maximum depth of 4.25 (14.0') was found with the top of the footing being flush with the mudline. The retrofit portion extended to 1.75m (5.7'.) A Level II cleaning was performed at the north-right and south-left quadrants, 1.0m (3.3') above the mudline.

PIER 4: A maximum depth of 4.25 (14.0') was found at the south nose with the retrofit portion extending to 1.75m (5.7') below the waterline. A Level II cleaning was performed at the north-left and south-right quadrants, 1.0m (3.3') above the mudline.

Except where mentioned, no exposure or other issues were found and the inspected portions of the substructure remain in good condition. This element will remain in condition state 1.

WATERWAY

Water surface elevation was recorded at 7.22m (23.6') from the waterline to the soffit at the right side of pier 2.

Prior to this inspection the NBI Item 61, Channel and Channel Protection, rating was 9. The conditions present on the date of this UWI are consistent with that coding.

UNDERWATER INVESTIGATION

Next Inspection: 18-JUN-2019 : 2 - Salt Water Type Max. Water Velocity: Inspection Freq.: 60 months 0 mps Dive Type : B - Routine UW Max. Water Depth : 4 m Dive Mode : D - Surface supplied Max. Visibility : 2.0 m Contractor : N/A Water Surface Elev.: Contract No. : N/A

Supervisor : Richard Hunt Diver : Jeremy Colby Tender : Dale Floyd Backup Diver : Mitch Miller

SUBSTRUCTURE INVESTIGATED

Location	Depth(m) Vel(mps) Channel	Substructure Description
Pier 2	3.5 0.0	Silty sand	RC hammerlead column (1)
Pier 3	4.3 0.0	Silty sand	RC hammerlead column (1)
Pier 4	3.3 0.0	Silty sand	RC hammerlead column (1)

ELEMENT INSPECTION RATINGS

Elem		Total		Qty in each Condition State					
No.	Element Description	Env	Qty	Units	St. 1	St. 2	St. 3	St. 4	St. 5
100000000000000000000000000000000000000	Concrete Deck - Unprotected w/ AC Overlay	3	520	sq.m	520	0	0	0	0
104 P	P/S Conc Closed Web/Box Girder	3	62	m.	62	0	0	0	0
	Reinforced Conc Column or Pile Extension	4	3	ea.	1	0	2	0	0
215 R	einforced Conc Abutment	2	24	m.	24	0	0	0	О
234 R	einforced Conc Cap	3	36	m.	36	0	0	0	0
256 S	lope Protection	3	2	ea.	2	0	0	0	0
312 E	nclosed/Concealed Bearing	3	1	ea.	1	0	0	0	0
335 O	ther Bridge Railing	2	140	m.	140	0	0	0	0

WORK RECOMMENDATIONS

RecDate: 02/22/2011 Action : Sub-Patch spalls EstCost: StrTarget:

Remove the unsound concrete clean and 2 YEARS patch the spalls at the splash zone of

No 38267

Work By: LOCAL AGENCY

DistTarget:

the north side of the piers.

Status : PROPOSED

EA:

Team Leader : Richard M. Hunt

Report Author: David Glasgow

Inspected By : D.Glasgow/RM.Hunt

Richard M. Hunt (Registered Civil Engineer)

(Date)

STRUCTURE INVENTORY AND APPRAISAL REPORT

	**************************************		**************************************
(1)	STATE NAME- CALIFORNIA 069		STATUS 51.0
(8)	STRUCTURE NUMBER 55C0561		
(5)	INVENTORY ROUTE (ON/UNDER) - ON 140000000		HEALTH INDEX 98.5
	HIGHWAY AGENCY DISTRICT 12		PAINT CONDITION INDEX = N/A
(3)	COUNTY CODE 059 (4) PLACE CODE 00000		******* CLASSIFICATION ******* CODE
3000000	FEATURE INTERSECTED- DANA POINT HARBOR	(112)	NBIS BRIDGE LENGTH- YES Y
	FACILITY CARRIED- ISLAND WAY		HIGHWAY SYSTEM- NOT ON NHS 0
	LOCATION- 0.1 MI S/O DANA PT HBR DR	400	FUNCTIONAL CLASS- LOCAL URBAN 19
	MILEPOINT/KILOMETERPOINT 0		DEFENSE HIGHWAY- NOT STRAHNET 0
10 - 10	BASE HIGHWAY NETWORK- NOT ON NET 0		PARALLEL STRUCTURE- NONE EXISTS N
			DIRECTION OF TRAFFIC- 2 WAY 2
000000000000000000000000000000000000000	LRS INVENTORY ROUTE & SUBROUTE	02/02/02/02/02	TEMPORARY STRUCTURE-
	LATITUDE 33 DEG 27 MIN 36.65 SEC		period region de destruction de la contraction d
0.0000000000000000000000000000000000000	LONGITUDE 117 DEG 41 MIN 57.47 SEC		
(98)	BORDER BRIDGE STATE CODE % SHARE %		DESIGNATED NATIONAL NETWORK - NOT ON NET 0
(99)	BORDER BRIDGE STRUCTURE NUMBER		TOLL- ON FREE ROAD 3
8.5	****** STRUCTURE TYPE AND MATERIAL ******		MAINTAIN- COUNTY HIGHWAY AGENCY 02
4000000	STRUCTURE TYPE MAIN: MATERIAL- PRSTR CONC CONT		OWNER- COUNTY HIGHWAY AGENCY 02
(43)	TYPE- BOX BEAM OR GIRDER - MULTI CODE 605	(37)	HISTORICAL SIGNIFICANCE- NOT ELIGIBLE 5
(44)	STRUCTURE TYPE APPR: MATERIAL- OTHER/NA		********* CODE
	TYPE- OTHER/NA CODE 000	(58)	DECK 7
(45)	NUMBER OF SPANS IN MAIN UNIT 4	(59)	SUPERSTRUCTURE 8
(46)	NUMBER OF APPROACH SPANS 0	(60)	SUBSTRUCTURE 6
(107)	DECK STRUCTURE TYPE- PRECAST CONC. PA CODE 2	(61)	CHANNEL & CHANNEL PROTECTION 9
	WEARING SURFACE / PROTECTIVE SYSTEM:	(62)	CULVERTS
	TYPE OF WEARING SURFACE- BITUMINOUS CODE 6		****** LOAD RATING AND POSTING ****** CODE
	TYPE OF MEMBRANE- NONE CODE 0	(24)	
	TYPE OF DECK PROTECTION- NONE CODE 0		DESIGN LOAD- UNKNOWN 0
	****** AGE AND SERVICE *********		OPERATING RATING METHOD- NO RATING ANALYSIS 5
(0.71)		117-100-1-120	OPERATING RATING- 53.5
	YEAR BUILT 1970	(65)	INVENTORY RATING METHOD- NO RATING ANALYSIS 5
	YEAR RECONSTRUCTED 0000	(66)	INVENTORY RATING- 32.6
(42)	TYPE OF SERVICE: ON- HIGHWAY-PEDESTRIAN 5 UNDER- WATERWAY 5	(70)	BRIDGE POSTING- EQUAL TO OR ABOVE LEGAL LOADS 5
(28)	LANES:ON STRUCTURE 02 UNDER STRUCTURE 00	(41)	STRUCTURE OPEN, POSTED OR CLOSED- A
	AVERAGE DAILY TRAFFIC 3510		DESCRIPTION- OPEN, NO RESTRICTION
	YEAR OF ADT 2011 (109) TRUCK ADT 1 %		******* APPRAISAL ********* CODE
			BAN SY HOUSEAN HOUSEAN FORM TO SEE
			STRUCTURAL EVALUATION 6 DECK GEOMETRY
	********** GEOMETRIC DATA **********	0.0000000000000000000000000000000000000	-
(48)	LENGTH OF MAXIMUM SPAN 15.2 M		UNDERCLEARANCES, VERTICAL & HORIZONTAL N
(49)	STRUCTURE LENGTH 62.2 M		WATER ADEQUACY APPROACH ROADWAY ALIGNMENT 8
(50)	CURB OR SIDEWALK: LEFT 1.5 M RIGHT 1.5 M		Moreover, and remaining the property of the control
(51)	BRIDGE ROADWAY WIDTH CURB TO CURB 8.5 M	250000000000000000000000000000000000000	TRAFFIC SAFETY FEATURES 1000
(52)	DECK WIDTH OUT TO OUT 12.5 M	(113)	SCOUR CRITICAL BRIDGES 5
(32)	APPROACH ROADWAY WIDTH (W/SHOULDERS) 8.5 M		******* PROPOSED IMPROVEMENTS *******
(33)	BRIDGE MEDIAN- NO MEDIAN 0	(75)	TYPE OF WORK- CODE
(34)	SKEW 0 DEG (35) STRUCTURE FLARED NO	(76)	LENGTH OF STRUCTURE IMPROVEMENT M
(10)	INVENTORY ROUTE MIN VERT CLEAR 99.99 M		BRIDGE IMPROVEMENT COST
(47)	INVENTORY ROUTE TOTAL HORIZ CLEAR 8.5 M	(95)	ROADWAY IMPROVEMENT COST
(53)	MIN VERT CLEAR OVER BRIDGE RDWY 99.99 M	* 500-54	TOTAL PROJECT COST
(54)	MIN VERT UNDERCLEAR REF- NOT H/RR 0.00 M		YEAR OF IMPROVEMENT COST ESTIMATE
(55)	MIN LAT UNDERCLEAR RT REF- NOT H/RR 0.0 M		
(56)	MIN LAT UNDERCLEAR LT 0.0 M		
32	*********** NAVIGATION DATA *********	(113)	AND STATE OF

	NAVIGATION CONTROL- NO CONTROL CODE 0 PIER PROTECTION- CODE	(90)	INSPECTION DATE 02/11 (91) FREQUENCY 48 MO
		(92)	CRITICAL FEATURE INSPECTION: (93) CFI DATE
	William I film Difficial Wall Will William Giffic	A)	FRACTURE CRIT DETAIL- NO MO A)
		B)	UNDERWATER INSP- YES 60 MO B) 06/14
(40)	NAVIGATION HORIZONTAL CLEARANCE 0.0 M	C)	OTHER SPECIAL INSP- NO MO C)