OC PUBLIC WORKS DEPARTMENT

JAMES TREADAWAY, DIRECTOR OF PUBLIC WORKS



HEWES MIDDLE

DODGE AVE.

D PUNCHED BOAT SPIKE


WASHER STAMPED 'LS 9305'

& 1-3/8 INCH BRASS

FLUSH WITH A.C.

2225856.18

6088813.22




SENIOR LAND SURVEYOR'S CERTIFICATE:

THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH REQUIREMENTS OF THE PROFESSIONAL LAND SURVEYOR'S ACT; THIS 24 DAY OF SEPTEMBER, 2024.

Ellit Medius

ELLIOTT MEDINA, PLS. SENIOR LAND SURVEYOR



SENIOR LAND SURVEYOR'S CERTIFICATE:

THIS MAP HAS BEEN EXAMINED IN ACCORDANCE WITH THE PROFESSIONAL LAND SURVEYORS' ACT; THIS 24 DAY OF SEPTEMBER, 2024.


SENIOR LAND SURVEYOR

David Bush

DocuSigned by:

478E777ED70B4AD... DAVID BUSH, PLS.


> FOUND CGPS "SACY" N: 2218016.19 E: 6061432.26 THIS IS A CONTINUOUS GPS STATION



FOUND CGPS "CCCS" N: 2261350.67

THIS IS A CONTINUOUS GPS STATION

(CGPS) AND IS PART OF THE CALIFORNIA



(CGPS) AND IS PART OF THE CALIFORNIA SPATIAL REFERENCE NETWORK (CSRN).

TOPOGRAPHIC MAPPING PROJECT



BASIS OF BEARINGS

THE BASIS OF BEARINGS FOR THIS SURVEY IS A LINE BETWEEN CONTINUOUS

HORIZONTAL DATUM

THIS COMBINATION FACTOR WAS DERIVED BY AN AVERAGE OF POINTS:

N: 2227353.77 E: 6088925.86 ELEVATION=241.08

N: 2225856.18 E: 6088813.22 ELEVATION=224.35'

ALL DISTANCES ARE BASED ON THE U.S. SURVEY FOOT.

VERTICAL DATUM

O.C.S. BM. 3C-22-71 ELEV. = 174.752' YEAR LEVELED: 2015

NAVD 1988 (O.C.S. 1995 ADJUSTMENT)

DESCRIPTION: MONUMENT IS SET IN KNOWN SUBSIDENCE ZONE AND MAY NOT FIT ADJACENT BENCHMARKS. DESCRIBED BY OCS 2001 - FOUND 3 3\4" OCS ALUMINUM BENCHMARK DISK STAMPED "3C-22-71", SET IN THE TOP OF A 4 IN. BY 4 IN. CONCRETE POST. MONUMENT IS LOCATED IN THE SOUTHEAST CORNER OF THE INTERSECTION OF LAMBETH WAY AND 17TH STREET, 43 FT. SOUTHERLY OF THE CENTERLINE OF 17TH STREET AND 42.6 FT. EASTERLY OF THE CENTERLINE OF LAMBETH WAY. MONUMENT IS SET UP 0.1 FT. FROM THE TOP OF CURB.

NOTES

THE SURVEY INFORMATION SHOWN HEREON IS TO BE USED FOR TOPOGRAPHIC RELATIONSHIPS ONLY AND IS NOT INTENDED FOR LAND ACQUISITION OR BOUNDARY PURPOSES.

SHEET INDEX


SHEET SHEET 2 SHEETS 3-4

TITLE SHEET BOUNDARY MAP TOPOGRAPHIC MAP


PURPOSE OF SURVEY

THE PURPOSE OF THE SURVEY IS TO PROVIDE A TOPOGRAPHIC MAP AND RIGHT OF WAY ESTABLISHMENT ALONG HEWES AVE BETWEEN FOOTHILL BLVD AND DEEP WELL RD.

			COUNTY OF ORANGE OC PUBLIC WORKS OC SURVEY/FIELD SERVICES/BOUNDARY ANALYSIS &					
			HEWES MIDDLE SCHOOL					
				TIT	LE SHEET			
			PROJECT LIMITS: FR	OM INTERSECTION OF	SECTION OF HEWES AVE AND FOOTHILL BLVD			
			TO INTERSECTION O	F HEWES AVE AND D	EEP WELL RD	BLVD		
			DATE OF SURVEY:08/27/2024 MAPPING		BY:R. BELTRAN & CREW	SHEET NO.		
					BY:P. MAGUIRE, PLS	SITELT IVO.		
			OFFICE CHECK		BY: D. BUSH, PLS] 1		
MARK	DATE	ITEM	FIELD CHECK		BY: R. BELTRAN & CREW	of		
REVISIONS			SCALE: N.T.S.	W.O. #ER20268	FILE #2425PW-ENG0002	4		
			FILE-HEWES TOPO 2024 DWG					







MONUMENT NOTES

- 1 FOUND PUNCHED HEX BAR PER (R11)&(R12), DOWN 1.4' IN O.C.S. WELL MONUMENT. ACCEPTED AS CENTERLINE INTERSECTION OF HEWES AVENUE AND FAIRHAVEN AVENUE.
- [2] FOUND PUNCHED HEX BAR PER (R11), DOWN 1.05 FEET, O.C.S. WELL MONUMENT HOUSING MISSING, S85°42'06"E 0.09" FROM THE SE'LY CORNER OF LOT 35 OF (R1).
- [3] FOUND PUNCHED HEX BAR IN O.C.S. WELL MONUMENT PER (R11) AND (R13), DOWN 1.2 FEET. ACCEPTED AS CENTERLINE INTERSECTION OF HEWES AVENUE AND DODGE AVE (NORTH).
- 4 FOUND PUNCHED BOAT SPIKE AND 1 3/8 INCH BRASS WASHER STAMPED "L.S. 9305", PER (R14), FLUSH IN AC. ACCEPTED AS THE CENTERLINE INTERSECTION OF HEWES AVE AND DODGE AVE (SOUTH).

ESTABLISHMENT NOTES

- ESTABLISHED THE CENTERLINE OF HEWES AVENUE BY HOLDING A LINE BETWEEN MONUMENTS 1 AND 4
- ESTABLISHED THE SE'LY RIGHT OF WAY OF HEWES AVENUE BY HOLDING A LINE PARALLEL WITH, AND A RECORD DISTANCE OF 50 FEET PER (R20) SE'LY FROM LINE ESTABLISHMENT (A).
- ESTABLISHED THE SE'LY CORNER OF LOT 35 OF (R1) BY HOLDING A POINT PERPENDICULAR TO MONUMENT 2 ON LINE ESTABLISHMENT 4.
- ESTABLISHED THE INTERSECTION OF VALE AVENUE AND HEWES AVENUE OF (R23) BY HOLDING A RECORD DISTANCE OF 972.15' PER (R21) FROM MONUMENT 1 S'LY ALONG ESTABLISHMENT (A).
- E ESTABLISHED THE CENTERLINE VALE AVENUE OF (R21) BY HOLDING A RECORD ANGLE PER (R23) W'LY FROM ESTABLISHMENT A AT ESTABLISHMENT .
- ESTABLISHED THE INTERSECTION OF SPAULDING AVENUE AND HEWES AVENUE OF (R23) BY HOLDING A RECORD DISTANCE OF 340.70' PER (R23) FROM ESTABLISHMENT (S'LY ALONG ESTABLISHMENT ()

ESTABLISHED THE CENTERLINE SPAULDING AVENUE OF (R23) BY HOLDING A

- RECORD ANGLE PER (R21) W'LY FROM ESTABLISHMENT AT ESTABLISHMENT .
- (H) ESTABLISHED THE INTERSECTION OF FOOTHILL BOULEVARD AND HEWES AVENUE OF (R25) BY HOLDING A RECORD DISTANCE OF 1084.42' PER (R25) FROM MONUMENT 4 S'LY ALONG ESTABLISHMENT A.
- ESTABLISHED THE CENTERLINE FOOTHILL BOULEVARD OF (R24) BY HOLDING A RECORD ANGLE PER (R10) E'LY FROM ESTABLISHMENT (A) AT ESTABLISHMENT .

NOTES

S.F.N. - SEARCHED, FOUND NOTHING

CALC FROM RECORD MAP

RECORD MAP

ALL BOUNDARY LINES NOT SHOWN IN BOLD ARE FOR GRAPHICAL REPRESENTATION

RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THE DOCUMENT OF RECORD. DISTANCES MAY BE EITHER GRID OR GROUND, AS PER SAID RECORD.

REFERENCE DOCUMENTS IN THE REFERENCE LEGEND ARE LIVE HYPERLINKS TO SAID DOCUMENT.

MONUMENT SYMBOLS CONTAIN LIVE HYPERLINKS TO IMAGES, IF THEY EXIST, OF RESPECTIVE MONUMENT.

BASIS OF BEARINGS

THE BASIS OF BEARINGS FOR THIS SURVEY IS A LINE BETWEEN CONTINUOUS GLOBAL POSITIONING STATIONS (SACY) AND (CCCS) BEING NORTH 12° 58' 34.1" EAST AS DERIVED FROM THE COORDINATES PUBLISHED BY THE CALIFORNIA SPATIAL REFERENCE CENTER (CSRC) ALONG WITH DATA SHEETS ON FILE IN THE OFFICE OF THE ORANGE COUNTY SURVEYOR.

HORIZONTAL DATUM

COORDINATES SHOWN ARE BASED ON THE CALIFORNIA COORDINATE SYSTEM (CCS83), ZONE VI, NAD 83, OCS (2017.50) EPOCH ADJUSTMENT. ALL DISTANCES SHOWN ARE GRID, UNLESS OTHERWISE NOTED. TO OBTAIN

GROUND DISTANCES MULTIPLY GRID BY A COMBINED FACTOR OF 1.00002320.

THIS COMBINATION FACTOR WAS DERIVED BY AN AVERAGE OF POINTS:

#3725

N: 2227353.77 E: 6088925.86 ELEVATION=241.08'

N: 2225856.18 E: 6088813.22 ELEVATION=224.35'

AS SHOWN ON SHEET 1.

ALL DISTANCES ARE BASED ON THE U.S. SURVEY FOOT.

	LINE TABLE								
LINE #	BEARING	MEASURED DISTANCE	RECORD DISTANCE						
L1	N04°17'54"E	177.73	177.72' (R10)						
L2	N42°25'48"W	27.42'	27.42' (R26)						

			OC SURVEY/	COUNTY OF ORANGE OC PUBLIC WORKS OC SURVEY/FIELD SERVICES/BOUNDARY ANALYSIS & MAPPING				
			HI	HEWES MIDDLE SCHOOL				
				BOUNDARY MAP				
			PROJECT LIMITS: F	PROJECT LIMITS: FROM INTERSECTION OF HEWES AVE AND FOOTHILL BLVD				
			TO INTERSECTION (TO INTERSECTION OF HEWES AVE AND DEEP WELL RD				
			DATE OF SURVEY:	:08/27/2024	BY:R. BELTRAN & CREW	SHEET NO.		
			MAPPING		BY: P. MAGUIRE, PLS	JILLI NO.		
			OFFICE CHECK		BY: D. BUSH, PLS	\rceil 2		
MARK	DATE	ITEM	FIELD CHECK		BY: R. BELTRAN & CREW	of		
REVISIONS			SCALE:1"=100'	W.O. #ER20268	FILE #2425PW-ENG0002	1		

FILE: HEWES_BOUNDARY_2024. DWG

REVISIONS

