City ofUNINCORPORATED TERRITORY Correct Legal DescriptionAT THE APPARENT INTERSECTION CORNER TYPE Government Corner Control Meander Property Rancho Other Date of Survey10-24-2022	N	COORDINATES (Optional) E. Metric U.S. Survey Foot m Epoch Date ublic Resources Code §§8801-8819 ublic Resources Code §§8890-8902 Other: Pre-Construction Post-Construction Security of the control of the con		
CORNER TYPE Government Corner ☐ Control ☐ Meander ☐ Property ☐ Rancho ☒ Other ☐ Date of Survey 10—24—2022 PLS Act Ref: ☐ 8765(d) ☒ 8771 Corner/ ☐ Left as found ☐ Established Monument: ☐ Found and tagged ☒ Reestablished Narrative of corner identified and monument as found, set, reset, ☒ See sheet #2 for description (s): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHO PARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOMEASURED DISTANCES SHOWN HEREON ARE GRID DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD MEASUREMENTS. SURVEYOR'S STATEMENT	N	AND BROWNING AVE COORDINATES (Optional) E. Metric U.S. Survey Foot m Epoch Date Ablic Resources Code §§8801-8819 Ablic Resources Code §§8890-8902 Other: Pre-Construction Post-Construction C: BOUNDARY LOCATIONS. RIGHT OF RIGHTS ARE DISPLAYED FOR GRAPH SHIP ONLY. M POSITIONS ESTABLISHED BY A FUSED THROUGH OR DOUBLE DETERMING DISTANCE, MULTIPLY A GRID DISTANCE, MULTIPLY A GRID DISTANCED. DISTANCES MAY BE EITHER GROON AND THE CONTRANCES MAY BE EITHER GROON AND THE CONTRA		
CORNER TYPE Government Corner Control Meander Property Rancho Other Date of Survey 10-24-2022 PLS Act Ref: 8765(d) 8771 Corner/ Left as found Established Monument: Found and tagged Reestablished Narrative of corner identified and monument as found, set, reset, See sheet #2 for description (s): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOP ARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOMEASURED DISTANCES, SHOWN HEREON ARE GRID DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD MEASUREMENTS. SURVEYOR'S STATEMENT	N	COORDINATES (Optional) E. Metric U.S. Survey Foot m Epoch Date ublic Resources Code §§8801-8819 ublic Resources Code §§8890-8902 Other: Pre-Construction Post-Construction Secure Displayed for graph Ship Only. M POSITIONS ESTABLISHED BY A FUSED THROUGH OR DOUBLE DETERMING DISTANCE, MULTIPLY A GRID DISTANCE, MULTIPLY A GRID DISTANCE, MULTIPLY A GRID DISTANCES MAY BE EITHER GRIPPORT A STANCES MAY BE EITHER GRIPPORT A		
Government Corner ☐ Control ☐ Meander ☐ Property ☐ Rancho ☑ Other Date of Survey 10-24-2022 PLS Act Ref: ☐ 8765(d) ☑ 8771 Corner/ ☐ Left as found ☐ Established ☐ Reestablished ☐ Found and tagged ☑ Reestablished ☐ Found and tagged ☑ Reestablished ☐ Sarrative of corner identified and monument as found, set, reset, ☑ See sheet #2 for description (\$): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOPARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOMEASURED DISTANCES SHOWN HEREON ARE GRID DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD MEASUREMENTS. SURVEYOR'S STATEMENT	N	EE		
Meander	Units Horizontal Datur Zone Vertical Datum Complies with Pu Complies with Pu 8773 Rebuilt Referenced replaced, or removed OWN HEREON TO TRUE CATION OF PROPERTY I	Epoch Date Boundary Locations. Right of Rights are displayed for Graph Only. M POSITIONS ESTABLISHED BY A FUSED THROUGH OR DOUBLE DETERMINED DISTANCE, MULTIPLY A GRID DISTANCE, MULTIPLY A GRID DISTANCES MAY BE EITHER G		
Date of Survey 10−24−2022 PLS Act Ref: □ 8765(d) □ 8771 Corner/ □ Left as found □ Established □ Reestablished □ Repartive of corner identified and monument as found, set, reset, □ See sheet #2 for description (s): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOWN OF ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOR MEASURED DISTANCES SHOWN HEREON ARE GRID DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD OF MEASUREMENTS. SURVEYOR'S STATEMENT	Horizontal Datur Zone Vertical Datum Complies with Pu Complies with Pu 8773 Rebuilt Referenced replaced, or removed WWN HEREON TO TRUE CATION OF PROPERTY INVENSE FROM WERE EITHER TRAVERS TO OBTAIN A GROUND HE DOCUMENT OF RECO	Epoch Date Epoch Date Ablic Resources Code §§8801-8819 Ablic Resources Code §§8890-8902 Other: Pre-Construction Post-Construction BOUNDARY LOCATIONS. RIGHT OF RIGHTS ARE DISPLAYED FOR GRAPH SHIP ONLY. M POSITIONS ESTABLISHED BY A FUSED THROUGH OR DOUBLE DETERMING DISTANCE, MULTIPLY A GRID DISTANCE, MULTIPLY A GRID DISTANCE. DRD. DISTANCES MAY BE EITHER G		
Date of Survey 10-24-2022 PLS Act Ref: 8765(d) 8771 Corner/ Left as found Sestablished Monument: Found and tagged Reestablished Narrative of corner identified and monument as found, set, reset, See sheet #2 for description (\$): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOUND PARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOR MEASURED DISTANCES SHOWN HEREON ARE GRID DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD OF MEASUREMENTS. SURVEYOR'S STATEMENT	Zone	Epoch Date Sublic Resources Code §§8801-8819		
PLS Act Ref: 8765(d) 8771 Corner/ Left as found Established Monument: Found and tagged Reestablished Narrative of corner identified and monument as found, set, reset, See sheet #2 for description (s): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOP PARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOR MEASURED DISTANCES, SHOWN HEREON ARE GRID DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD OF MEASUREMENTS.	Complies with Pull Complies with Pull Complies with Pull 8773 Rebuilt Referenced replaced, or removed Tation of Property Invense From Were Either Travers To Obtain a Ground Be Document of Recomplies.	Ablic Resources Code §§8801-8819 Ablic Resources Code §§8890-8902 Other: Pre-Construction Post-Construction BOUNDARY LOCATIONS. RIGHT OF RIGHTS ARE DISPLAYED FOR GRAP SHIP ONLY. M POSITIONS ESTABLISHED BY A FISED THROUGH OR DOUBLE DETERM DISTANCE, MULTIPLY A GRID DIST DRD. DISTANCES MAY BE EITHER GRAP		
Corner/ Cor	Complies with Pu	Diblic Resources Code §§8890-8902 Other: Pre-Construction Post-Construction BOUNDARY LOCATIONS. RIGHT OF RIGHTS ARE DISPLAYED FOR GRAP SHIP ONLY. M POSITIONS ESTABLISHED BY A FISED THROUGH OR DOUBLE DETERM DISTANCE, MULTIPLY A GRID DISTORD. DISTANCES MAY BE EITHER GOOD.		
Corner/ Left as found Established Monument: Found and tagged Reestablished Varrative of corner identified and monument as found, set, reset, See sheet #2 for description (s): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOP PARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOR MEASURED DISTANCES SHOWN HEREON ARE GRID DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD MEASUREMENTS. SURVEYOR'S STATEMENT	Rebuilt Referenced replaced, or removed OWN HEREON TO TRUE CATION OF PROPERTY I R ANGULAR RELATIONS IVED BY INVERSE FROM WERE EITHER TRAVERS TO OBTAIN A GROUND HE DOCUMENT OF RECO	Pre-Construction Post-Construction BOUNDARY LOCATIONS. RIGHT OF RIGHTS ARE DISPLAYED FOR GRAPH ONLY. M POSITIONS ESTABLISHED BY A FUSED THROUGH OR DOUBLE DETERM DISTANCE, MULTIPLY A GRID DISTANCE.		
Monument: Found and tagged Reestablished Narrative of corner identified and monument as found, set, reset, See sheet #2 for description (s): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOPARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOM MEASURED DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD OF MEASUREMENTS. SURVEYOR'S STATEMENT	Referenced replaced, or removed WIN HEREON TO TRUE CATION OF PROPERTY I R ANGULAR RELATIONS IVED BY INVERSE FROM WERE EITHER TRAVERS TO OBTAIN A GROUND HE DOCUMENT OF RECO	Post-Construction d: BOUNDARY LOCATIONS. RIGHT OF RIGHTS ARE DISPLAYED FOR GRAPH ONLY. M POSITIONS ESTABLISHED BY A FISED THROUGH OR DOUBLE DETERM DISTANCE, MULTIPLY A GRID DISTANCE, MULTIPLY A GRID DISTANCE.		
See sheet #2 for description (s): NO CLAIM IS MADE AS TO THE RELATIONSHIP OF THE POINTS SHOPARCEL, OR LOT LINES, OR ANY OTHER DATA RELATED TO DELINE REPRESENTATION ONLY. BEARINGS SHOWN HEREON ARE ASSUMED AND ARE DISPLAYED FOR MEASURED DISTANCES, DER MEASURED DISTANCES, DER REDUNDANT LEAST SQUARES NETWORK ADJUSTMENT. ALL POINTS PER CHAPTERS 5 & 11 OF THE OC SURVEY STANDARDS MANUAL. BY 1.00002370. RECORD DISTANCES SHOWN HEREON ARE AS THEY APPEAR ON THOR GROUND, AS PER SAID RECORD. ALL DISTANCES WERE FIELD OF MEASUREMENTS. SURVEYOR'S STATEMENT	OWN HEREON TO TRUE CATION OF PROPERTY I R ANGULAR RELATIONS IVED BY INVERSE FROM WERE EITHER TRAVERS TO OBTAIN A GROUND HE DOCUMENT OF RECO	BOUNDARY LOCATIONS. RIGHT OF RIGHTS ARE DISPLAYED FOR GRAP SHIP ONLY. M POSITIONS ESTABLISHED BY A FISED THROUGH OR DOUBLE DETERM DISTANCE, MULTIPLY A GRID DISTORD. DISTANCES MAY BE EITHER OF THE POSITION		
the Professional Land Surveyors' Act on02-14		SED LAND SURL		
0.3.03		FOF CALIFOR		
COUNTY SURVEYOR'S STATEMENT This Corner Becard was received 02-14-2023				
This comer record was received	SED LAND SUPLATION OF THE LAFON			
and examined and filed 11-13-2023				
Signed (P.L.S.)o	r R.C.E. No. <u>8970</u>	\\^\		
Title DEPUTY COUNTY SURVEYOR		NO. 8970 NO. 8970 PAR OF CALIFORN		
County Surveyor's Comment				

- (1) SEARCHED, FD NOTHING; SET SPIKE & 1-1/2" SS WSHR STMPD "OCS", FLUSH IN AC PER TIES AS SHOWN HEREON
- 2 FD LEAD & 3/4" BR TAG STMPD "OCS TIE" ON TOP OF CONC CURB, PER R1
- FD MONUMENT AS DESCRIBED ON ADJACENT CORNER RECORD
- (4) APPARENT TRACT BOUNDARY, SFN

	LINE #	MEAS & REC BEARING	MEAS & REC DISTANCE	REF			
	L1	N71°21'38"E	35.68'	R1			
	L2	N04°39'05"W	61.63'	R1			
	L3	N64°01'13"E	46.39'	R1			
	L4	N27°02'04"W	48.08'	R1			
	L5	N58°47'58"E	58.65'	R1			
	L6	N26°42'17"W	47.52'	R1			
	L7	N86°57'54"E	25.38'	R1			
	L8	N05°04'57"W	62.05'	R1			
	L9	N40°38'29"E	190.00'	R1			
	L10	N40°45'23"E	25.06'	R1			
	L11	N40°38'18"E	445.21'	R1			
	L12	N49°20'35"W	74.28'	R1			
	L13	N49°18'21"W	90.00'	R1			
2	2						